


RoadRunner Series


Standard electronic controllers for
Automotive, Avionic and Marine
SPD windows



Automotive Controllers

SCSC Intelligent RoadRunner Automotive Controllers are targeted for the automotive industry but are easily adapted for avionic and marine environments to control SPD glass or plastic windows. This flexible, highly configurable, customizable, feature rich series of electronic controllers bring SPD windows to life and easily integrate with other control systems. Used in cars, aircraft, boats and other custom applications, the controller operates single or multiple SPD windows by several different methods:

- Manual operations via dimmers and solid-state slide switches
- Automatic control through coordination with on-board systems
- Self regulated control via sensors



SPD Control Systems Corp.
25 Health Sciences Drive – Suite 212B
Stony Brook, New York 11770
(631) 776-8500 (office)
(631) 776-8501 (fax)
www.spdControlSystems.com
sales@spdControlSystems.com

RoadRunner



Revolution SPD Smart Glass Controllers

ROADRUNNER Automotive Series

The **RoadRunner Automotive Controllers** by SPD Control Systems Corporation (SCSC) are standardized stand-alone electronic controllers designed to operate automotive SPD Smart Glass windows. **Roadrunner** provides a comprehensive set of options for connectivity. **Note:** The Roadrunner controller is easily customized to our client's exact needs.


Versions

- 1-window
- 8-window

Features

- Small footprint circuit board controller or control module
- Interfaces to standard automotive control systems
- Manual control via support of an array of input devices
- Automatic control via photocell light sensor, rain sensors and others
- Automatic mode for seasonal and time of day settings
- Battery backup for power fail operations (optional)
- Customizable for a wide-range of special projects
- Configurable setting for SPD state when vehicle is turned off

Roadrunner Controller Connectivity



RoadRunner

Images of the 8-Window Automotive Controller

RoadRunner Demo Setup at the RFI 2008 Annual Meeting



View video – www.spdControlSystems.com/RoadrunnerDemo.htm



RoadRunner

Specifications

	1-Window	8-Window	Comment
General			
Microprocessor	Freescale HCS08 Family		
Software Environment	Proprietary Real time Scheduler		
Customizable Software Applications	yes		
Customizable Hardware	yes		
Power-up Diagnostics	yes		
Status Check/Diagnostic Command Set	yes		

Film Characteristics			
Normalize Tint Level	yes		Supports all SPD film types / characteristics. Provides linear opaque control of SPD film regardless its electrical non-linearity.
Max. Number of Windows	1	8	
Max. Number of SPD Film Segments	2	16	A single piece of glass may consist of multiple film segments.
Max. Size Film for Each Window	16 sq. ft (1.2 M ²)		
Output Voltage	30 – 120VAC RMS		
Output Isolation	yes		AC output electrically isolated from the vehicle power source
Maximum Window Output Current	30 mA per window		
SPD Film Frequency	30Hz to 400Hz		60 Hz is used on the evaluation controller. There may be film produced requiring a higher frequency and there are special cases where a higher or lower frequency may be desirable
Window Tint Transition Time	1 to 2 seconds for 95% of change		

Power			
DC	7.5 VDC input to 17 VDC input nominal		
Max Power Consumption	tbd	48 watts	All 8 windows in the clear state.
Typical Power Consumption	tbd	tbd	Based on the size and number of windows.
Backup power	optional battery		

